

BGC-2300

ADVANCED FILTRATION TECHNOLOGY

This BevGuard™ brand water filter contains a compressed carbon block, which provides tremendous capacity to remove and/or reduce impurities and sediment that may be present in your drinking water. The carbon block has millions of active sites on its surface and within the structure which can absorb impurities like a sponge, and can attract and hold other types of impurities to its surface like a magnet. Additionally, this filter can catalytically breakdown other impurities very similar to the way a catalytic converter works in your automobile. These processes ensure that you are getting the cleanest and best tasting water possible.

This economical filter will provide you with fresh and clean tasting water for any beverage application.

REPLACES:

- M™/Cuno® CFS 8720 55893-03, CFS 517-LS 55584-01, AP517 55600-01, CS-62 55584-04, AP-DW85 55844-08

FILTER FEATURES:

- Economical alternative to expensive filter substitutes
- Delivers clean, clear water that looks and tastes great
- Will remove or reduce chlorine taste and odor that may be present in your drinking water
- Designed to provide up to twelve months of life or 10,000 gallons
- Does not remove minerals which may be beneficial to health

This filter should not be used with water that is microbiologically unsafe or of unknown quality, without adequate disinfection before and/or after the filter.

BevGuard™ filters have been tested by the manufacturer against ANSI/NSF Standard 42 for the reduction of chlorine taste and odor.

Micron Rating:	5 micron
Dimensions:	12 1/4" x 3 3/16" (3.11 cm x 8.1 cm)
Min Operating Pressure:	25 psi (1.7 bar)
Max Operating Pressure:	125 psi - (8.6 bar)
Operating Temperature:	35-100°F (1.7°C - 38°C)
Flow Rate:	1.67 gpm/6.32 lpm
Life:	12 months or 10,000 gallons (37,854 liters)

Cuno® is a registered trademark of the 3M Company™



BGC-2300 **BevGuard**
Food Service Water Filtration Technology

Sediment and Chlorine Reduction Cartridge
Exclusive BevGuard™ filtration media provides improved sediment and chlorine reduction with superior taste.

Specifications	
Dimensions:	12 1/4" x 3 3/16" (31.1 cm x 8.1 cm)
Operating Parameters:	25-125 psi (1.7-8.6 bar)
Operating Temperature:	35-100°F (1.7°C - 38°C)
Maximum Service Flow Rate:	1.67 gpm (6.32 lpm)
Filter Life:	12 Months or 10,000 gal (37,854 L)

Replace cartridge annually, or sooner, should flow become less than desirable. Cartridge capacity may vary according to flow rate, inlet line pressure and local water conditions, which may require more frequent cartridge replacement.
Check for compliance with state and local laws and regulations.

Cross Reference Guide	
BGC-2300	CFS 8720 55893-03, CFS 517-LS 55584-01, AP517 55600-01, CS-62 55584-04, AP-DW85 55844-08

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.
Meets or exceeds the performance of the cross referenced 3M™/Cuno™ product listed above.
Tested by the manufacturer to ANSI/NSF Standard 42 for the reduction of chlorine taste and odor.

BevGuard™
Customer Service (951) 541-9517 or Toll Free (866) 218-8473
Visit us on the web at www.bevguard.com
CUNO™ is a registered trademark of 3M Company™

